# **Datenblatt Cineflex V14 Sony 1500**

## **Professionelle High-Definition-Kamera**

Das kreiselstablisierte Cineflex V 14 System zeichnet sich durch einen Schwenkbereich von vollen 360° horizontal und von + 20° bis - 195° vertikal aus. Zudem gleicht die Kameraaufhängung Querneigungen des Hubschraubers von bis zu ± 45° aus, um den Horizont im Bild waagerecht zu halten.

Eine maximale Drehgeschwindigkeit von 55° pro Sek. erlaubt rasche Bildwechsel. Die Betriebsspannung des Systems beträgt 28 Volt DC.



## Kameraspezifikationen:

Model	Sony HDC-1500
Pickup device	3-CCD 2/3-inch type 16:9
Effective pixels	1920(H) X 1080(V)
Compression	4.4.4 can be switched to 4.2.2
Spectrum system	F1.4 prism system
Built in filters	1: Clear, 2: 1/4ND, 3:1/8ND, 4:1/16ND, 5: 1/64ND
	A: Cross, B: 3200K, C: 4300K, D: 6300K, E: 8000K
Servo filter control	Yes
Sensitivity	F10 at 2000 lx (3200K, 89.9% reflectance)
Signal-to-noise ratio	54dB (typical)
Horizontal	1000 TV lines
Video format	1080/60p-50p-30p, 1080/60i-50i, 1080/24p-25p
	720/60p-50p

HD Camera	
Model	Sony HDC-1500
Pickup device	3-CCD 2/3-inch type 16:9
Effective pixels	1920(H) X 1080(V)
Compression	4.4.4 can be switched to 4.2.2
Spectrum system	F1.4 prism system
Built in filters	1: Clear, 2: 1/4ND, 3:1/8ND, 4:1/16ND, 5: 1/64ND
	A: Cross, B: 3200K, C: 4300K, D: 6300K, E: 8000K
Servo filter control	Yes
Sensitivity	F10 at 2000 lx (3200K, 89.9% reflectance)
Signal-to-noise ratio	54dB (typical)
Horizontal	1000 TV lines
Video format	1080/60p-50p-30p, 1080/60i-50i, 1080/24p-25p
	720/60p-50p

Lens Options	
The camera system can be	adapted for multiple lens configurations upon request
Fujinon HA 42 X 13.5	(13.5mm to 1134mm optical, 2268mm digital)
Fujinon HA 42 X 9.7	(9.7mm to 815mm optical, 1630mm digital)
Fujinon HA 22 X 7.8	(7.8mm to 343mm optical, 686mm digital)
Fujinon HA 13 X 4.5	(4.5mm to 117mm optical, 234mm digital)



Sony HKC-T1500 CCD	Block Extension Adaptor
Sony RM-B750	LCD touch-panel screen, direct push buttons
	plus Memory Stick media card slot to recall
	setup parameters

The camera system can be	adapted for multiple lens configurations upon request
Fujinon HA 42 X 13.5	(13.5mm to 1134mm optical, 2268mm digital)
Fujinon HA 42 X 9.7	(9.7mm to 815mm optical, 1630mm digital)
Fujinon HA 22 X 7.8	(7.8mm to 343mm optical, 686mm digital)
Fujinon HA 13 X 4.5	(4.5mm to 117mm optical, 234mm digital)

Item	Weight	Dimensions
Turret (dependent on lens)	45-68 lbs.	14.5 x 19.5 x 19.5 in.
Auxiliary Control Unit	27 lbs.	14 x 19 x 6 in.
Laptop Control Unit	5 lbs	17 x 8.75 x 1.8 in
Cable Set	9 lbs	(20ft. length)

## Sie haben noch Fragen?

Rufen Sie uns an...



### **Euroheli Helicopterdienste GmbH**

In der Alting 7, 90596 Schwanstetten, Germany

Phone: +49 (0) 9170 - 972 50 - 0 +49 (0) 9170 - 972 50 - 15 Fax:

E-Mail: info@euroheli.de Web: www.euroheli.de